








**WHEELED**  
SERIES **960**



**SPECIFICATIONS**

<b>Interior dimensions</b>	L22.0 x W17.0 " x H12.9" L559mm x W432mm x H328mm
<b>Exterior dimensions</b>	L25.4" x W20.0" x H14.5" L645mm x W508mm x H368mm
<b>Weight (empty)</b>	19.2 lbs   8.7 kg
<b>Lid depth</b>	2.1"   53mm
<b>Base depth</b>	10.8"   274mm
<b>Max buoyancy</b>	167.6 lbs   76 kg
<b>Temperature range</b>	Min -20°F (-29°C) Max 140°F (60°C)
<b>Airline cabin carry-on</b>	No
<b>Watertight</b>	Yes - IP67
<b>Warranty</b>	Conditional lifetime guarantee

**CERTIFICATIONS**

-  IPX7 INGRESS PROTECTION - WATERPROOF
-  IP6X INGRESS PROTECTION - DUSTPROOF
-  ATA SPECIFICATION 300 - CATEGORY 1 IMPACT
-  48cm(19")  
min. ASTM D-4169 DC-18 - DROP TEST
-  ASTM D-4169 DC-18 - VIBRATION
-  ASTM D-4169 DC-18 - RAINFALL
-  1 meter  
(3.28 ft) MIL-STD-810F - IMMERSION

**MATERIALS**

- Case shell** – NK-7 high impact polypropylene
- Latches** – Nylon 66
- Handle** – NK-7 high impact polypropylene | TPE
- Purge valve** – Nylon 66 | Gore® membrane | Silicone washers
- Pins/hardware** – 304 stainless steel
- Gasket** – EPDM
- Backing plate** – NK-7 high impact polypropylene
- Pull handle** – Polycarbonate + ABS | Nylon | TPE
- Wheels** – Polyurethane | Polycarbonate

## STANDARD FEATURES

- 1 - Powerclaw latching system
- 2 - Waterproof IP67 rated
- 3 - Impact resistant NK-7 resin
- 4 - Reinforced metal padlock holes
- 5 - Stackable
- 6 - 2-stage retractable handle
- 7 - Polyurethane wheels
- 8 - Side mounted spring loaded handles
- 9 - Automatic pressure release valve
- 10 - Integrated lid stay
- 11 - Removable lid
- 12 - Top and bottom panel mount
- 13 - 100% stainless steel hardware
- 14 - Lifetime guarantee



## AVAILABLE COLORS



## AVAILABLE OPTIONS



## CUSTOM OPTIONS

